

Alloy Weave™

colour & design®

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg Woven	
	Material Width	54"	137 cm

Federal Specifications: Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification

Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 0; Smoke Developed: 10
Passes NFPA 286 Corner Burn Test

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with water-based inks
- Five year warranty against materials defects

Environmental Attributes:

- PVC-Free
- Declare Red List Free
- 15% Post-Consumer Recycled Content
- HDP Available

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.
Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

INSTALLATION NOTE

ALLOY WEAVE™ is a straight hang, random match
For specifications and hanging instructions go to: www.colouranddesign.com