



Type II

Physical Properties: Total Weight U.S. Units Metric Units

Fabric Type

20 oz./LY 619 G/PLM 13.3 oz./SQ 451 G/PSM

Poly Cotton Osnaburg

Material Width 52/54" 132/137 cm

Repeat Horizontal 27" x Vertical 24"

Federal Specifications: Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification

CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and

EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification

Results:

ASTM E-84 Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 10

Passes NFPA 286 Corner Burn Test

Performance Features: • Phthalate-free

· No heavy metals or formaldehyde

· Printed with low VOC inks

Five year warranty against materials defects

Environmental Attributes:

- Ultra-low emitting Pass rating under CA 01350
- · NSF/ANSI 342 certified for sustainability

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

INSTALLATION NOTE

BELLALINO™ is a non-reversible / random match

For specifications and hanging instructions go to: www.colouranddesign.com



www.colouranddesign.com

