

## Canyon Linen™

## Type II

| Physical Properties:                   | <b>Total Weight</b><br>Fabric Type<br>Material Width<br>Repeat  | <b>U.S. Units</b><br>20.0 oz./LY<br>13.3 oz./SQ<br>Non-woven<br>52/54″<br>Horizontal 53″ x Vertical 18 | Metric Units<br>619 G/PLM<br>451 G/PSM<br>132/137 cm |
|--|---|--|--|
| Federal Specifications:                | Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.  |  |  |
| Fire Hazard Classification<br>Results: | <b>ASTM E-84</b> Tunnel Test: Class A, Flame Spread: 5; Smoke Developed: 30<br>Passes NFPA 286 Corner Burn Test   |  |  |
| Performance Features:                  | <ul> <li>Phthalate-free</li> <li>No heavy metals or formaldehyde</li> <li>Printed with low VOC inks</li> <li>Five year warranty against materials defects</li> </ul>  |  |  |
| Environmental Attributes:              | <ul> <li>Ultra-low emitting – Pass rating under CA 01350</li> <li>NSF/ANSI 342 certified for sustainability</li> </ul>  |  |  |
| Permeability, Moisture and<br>Mold:    | Contains anti-microbial additives to resist the grown of mildew and bacteria and pass<br>ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in<br>excess of 4% and/or is allowed to accumulate in or behind the walls.<br>Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed<br>on walls that are susceptible to excessive condensation or moisture infiltration. |  |  |

## **INSTALLATION NOTE**

**Canyon Linen<sup>™</sup>** is a random match / reversible pattern For specifications and hanging instructions go to: www.denovowall.com



Copyright© 2020. All Rights Reserved Any copying or other use is expressly prohibited DeNovo Wall is a trademark.



MADE IN USA