

A custom, digitally printed wallcovering that is visual, magnetically receptive, and dry eraseable.



DIGITAL-MAG6 Digitally printable

- Flexible polyester and ferrous metal core wallcovering
- Cellulose non-woven backing
- Neodymium magnet receptive
- Digitally printable smooth surface
- Commercial quality wallcovering

Magnetically receptive wallcovering

- 60" width on 50ft roll length is standard packaging
- Easy install with plyability even around corners and columns
- Sold individually or as a system with dry erase coating
- On-site INFINITY application creates a seamless finish

functional

- Three Ways to get the most out of DIGITAL-MAG
 - DIGITAL-MAG
 - DIGITAL-MAG-COATED
 - DIGITAL-MAG-CD + COATED
- Suitable for corporations, schools, universities, healthcare, and a multitude of visual applications
- Determine your wall usage (print solid colour, images, logos, lettering, way finding, etc.)

convenient

- Choose your design option
- Choose your finish (coated/uncoated)
- Communicate your branding at every
- presentation
- Puts your feature walls to work

durable

- Easy to maintain
- 10-year limited warranty
- Guaranteed not to delaminate or yellow over time
- Lightweight for a minimal carbon footorint



warranty

DIGITAL-MAG is covered by a ten year limited warranty. This warrants that DIGITAL-MAG will be free from any defects in material or workmanship and meet the design criteria noted in our specifications when properly applied and installed per our recommended installation instructions. For more details on the DIGITAL-MAG warranty, please visit WriteWalls.global

Note: For best results, Neodymium magnets are recommended for DIGITAL-MAG.

physical properties of DIGITAL-MAG

| Product Code | Roll Size | Width | Backing | Film Weight | Fabric weight |
|--------------|------------------|------------------------|-----------------------------|-----------------|-----------------|
| DIGITAL-MAG | 50ft | 60" | 100% Cellulose Non-Woven | 0.95 oz / sq yd | 1.25 oz / sq yd |
| Composition | Total Weight | Flame Resistance | | | |
| PET | 27.50 oz / sq yd | Class A (ASTM E-84) | | | |