

# Impromptu



**AZ52970IM** Lemon Grass

54"/ Type II / 20 oz. **LOW VOC**

## **PHYSICAL PROPERTIES**

**Weight:** 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM

**Backing:** Osnaburg **Width:** 54 in./137 cm

**Match:** Reverse, random

Custom colors, weights, and micro venting available

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

## **FIRE SAFETY**

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

## **ENVIRONMENT & HEALTH**

- Contains 10% recycled content
- Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details
- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 point for regional materials

## **ANTIMICROBIAL FEATURES**

Symphony® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All Symphony® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

## **WARRANTY**

5 year warranty against manufacturing defects.

Additional information is available at: [symphonywallcovering.com](http://symphonywallcovering.com)