

Jemma™

de  
nōvō® WALL

Type II

---

**Physical Properties:**

Total Weight	U.S. Units	Metric Units
	20.0 oz./LY	619 G/PLM
	13.3 oz./SQ	451 G/PSM
Fabric Type	Poly Cotton Osnaburg	
Material Width	52/54"	132/137 cm
Repeat	Horizontal 27" x Vertical 24"	

---

**Federal Specifications:**

Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

---

**Fire Hazard Classification Results:**

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 15  
Passes NFPA 286 Corner Burn Test

---

**Performance Features:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

---

**Environmental Attributes:**

- Ultra-low emitting – Pass rating under CA 01350

---

**Permeability, Moisture and Mold:**

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.  
Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

**INSTALLATION NOTE**

Jemma™ is a random match, reversible pattern  
For specifications and hanging instructions go to: [www.denovowall.com](http://www.denovowall.com)

de  
nōvō® WALL

Tel: 501-372-3550 Fax: 501-372-3553  
[www.denovowall.com](http://www.denovowall.com)

Copyright© 2024. All Rights Reserved  
Any copying or other use is expressly prohibited  
DeNovo Wall is a trademark.

MADE IN USA