

Pawleys Island™

de

nōvō®

WALL

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Non-woven	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 52" x Vertical 24"	
<hr/>			
Federal Specifications:	Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.		
<hr/>			
Fire Hazard Classification Results:	ASTM E-84 Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 10 Passes NFPA 286 Corner Burn Test		
<hr/>			
Performance Features:	<ul style="list-style-type: none">• Phthalate-free• No heavy metals or formaldehyde• Printed with low VOC inks• Five year warranty against materials defects		
<hr/>			
Environmental Attributes:	<ul style="list-style-type: none">• Ultra-low emitting – Pass rating under CA 01350• NSF/ANSI 342 certified for sustainability		
<hr/>			
Permeability, Moisture and Mold:	Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.		

INSTALLATION NOTE

Pawleys Island™ is a non-reversible match pattern

For specifications and hanging instructions go to: www.denovowall.com