

HIGH PERFORMANCE FCO-FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

■ reated with Stain Guard. Stain Guard's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment investment for your customers.

PLAYLIST SPECIFICATIONS

13 07

CONTENT BACKING FINISH WEIGHT WIDTH ROLL SIZE

Stain Guard

96% polyester acrylic latex
4% metalized polyester varn

RECYCLED CONTENT

· up to 96% post-industrial content (varies by color, minimum 62%)

FLAMMABILITY

Class A / ASTM E-84 Passes: UBC 8-2 FS: 25 / SD: 25 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 51,000 double rubs

COLOR FASTNESS TO LIGHT

50 yards

54"

(AATCC-16A) exceeds Class 4.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- chlorene
- plasticizers
- · heavy metals
- · formaldehvde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce