

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance varns. Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

PRODUCTION SPECIFICATIONS

CONTENT

BACKING

FINISH

WEIGHT

WIDTH

ROLL SIZE

· 67% polvester

acrylic latex

CryptonWall® 'Green' 18 oz.

54"

50 vards

· 33% olefin

Soil & Stain Repellant

43% RECYCLED CONTENT

· 10% post-consumer (polyester) · 33% post-industrial (olefin)

ABRASION RESISTANCE

(ASTM D-4157-02) 100,000 double rubs **COLOR FASTNESS TO LIGHT**

(AATCC-16A) Class 5.0 / 40 hrs.

Class A / ASTM E-84 FS: 20 / SD: 50 Passes: Cal 117 Passes: Vertical Burn

FLAMMABILITY

Passes: NFPA 265

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

Greenquard Gold Certified

- · Number 23850-410
- · formerly Children & Schools Gold Certified
- meets Calif 1350 High Performance Schools