# **SANDRO**<sup>™</sup>

# LOW VOC TYPE II

## **PHYSICAL PROPERTIES:**

52"/54" (132/137 CM) Vinyl Wallcovering, Type II Total Weight: 20 oz./lin. yard (619 G/PLM) 13.3 oz./sq. yard (451 G/PSM) Backing: Osnaburg Horizontal 14-1/2" x Vertical 11-5/8" Repeat: All patterns are stocked in 30 linear yard bolts and must be ordered in 15 yard increments.

#### FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test Class "A" Fire Rated Flame Spread 15 Smoke Development 10

In addition, this product meets Type II CCC-W-408A through D & W-101 requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

#### **ENVIRONMENT & HEALTH:**

Meets California Section 01350 IAQ test requirements for wallcovering Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives Can contribute to LEED® MR 5.1 point for regional materials

All installations must conform to DeNovo's current Hanging Instructions and Product Technical information.

#### **ANTI-MICROBIAL FEATURES:**

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

### BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:

Breathe Free™ Micro-vented wallcovering from Denovo Wall can be used to help control un-wanted moisture inside a building envelope.

#### LIMITED WARRANTY:

5 year warranty against manufacturing defects. Additional information is available at www.denovowall.com



MADE IN USA

Tel: 501-372-3550 Fax: 501-372-3553 www.denovowall.com

INSTALLATION NOTE SANDRO<sup>™</sup> is a random match / reversible pattern

For specifications and hanging instructions go to: www.denovowall.com

Copyright© 2016. All Rights Reserved Any copying or other use is expressly prohibited DeNovo Wall is a trademark.

