PHYSICAL PROPERTIES:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Repeat: Horizontal 27" x Vertical 24"

All patterns are stocked in 30 linear yard bolts and must be ordered in 15 yard increments.

MYLAR COLOURS: CD2-SHO-25, CD2-SHO-34, CD2-SHO-35

Backing: Nonwoven • Class "A" Fire Rated • Flame Spread 25 • Smoke Development 55 These sku's are constructed with Mylar and have special installation instructions. Please visit our website at colouranddesign.com and download instructions prior to installation.

ALL REMAINING COLOURS

Backing: Osnaburg • Class "A" Fire Rated • Flame Spread 15 • Smoke Development 10

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

In addition, this product meets Type II CCC-W-408A through D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance

SUSTAINABILITY, ENVIRONMENT AND HEALTH:

Meets California 01350 IAQ test requirements for wallcovering

USGBC LEED

Can contribute to CI/NC LEED® EQ 4.1 Low Emitting Materials: Adhesives and Sealants. Can contribute to CI/NC LEED® EQ 4.2 Low Emitting Materials: Paints and Coatings. Can contribute to CI/NC LEED® MR 5.1 Regional Material: 20% manufactured regionally within 500 miles of jobsite. Can contribute to CI/NC LEED® MR 4 building Product Disclosure and Optimization: Published Health Product Declaration (HPD)

All installations must conform to Colour & Design's current Hanging Instructions and Product Technical information.

ANTI-MICROBIAL FEATURES:

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:

Breathe Free™ Micro-vented wallcovering from Colour & Design can be used to help control un-wanted moisture inside a building envelope.

Breathe Free™ Micro-vented wallcovering is not available for MYLAR COLOURS: CD2-SHO-25, CD2-SHO-34, CD2-SHO-35.

LIMITED WARRANTY:

5 year warranty against manufacturing defects.

INSTALLATION NOTE

Shilo[™] is a random match/reversible pattern

For specifications and hanging instructions go to: www.colouranddesign.com



TEL: 501-372-3550 FAX: 501-372-3553 www.colouranddesign.com Copyright © 2016 Colour & Design Inc. Any copying or other use is expressly prohibited All Rights Reserved



MADE IN USA