

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 52" x Vertical 18"	

Federal Specifications: Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 10
 Passes NFPA 286 Corner Burn Test

- Performance Features:**
- Phthalate-free
 - No heavy metals or formaldehyde
 - Printed with low VOC inks
 - Five year warranty against materials defects

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350

Permeability, Moisture and Mold: Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

INSTALLATION NOTE
 Silk Street™ is a random reversible pattern
 For specifications and hanging instructions go to: www.denovowall.com