

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns. Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

14 oz.

WATTAGE **SPECIFICATIONS**

CONTENT **BACKING FINISH ROLL SIZE WEIGHT** WIDTH

CryptonWall® 'Green' acrylic latex · 80% polyester Soil & Stain

· 20% olefin Repellant

46% RECYCLED CONTENT

· 11% post-consumer (polyester)

Passes: UBC 8-2 Corner Burn

· 35% post-industrial (15% polyester, 20% olefin)

FLAMMABILITY

Class A / ASTM E-84 FS: 20 / SD: 50 Passes: Cal 117 Passes: Vertical Burn ABRASION RESISTANCE

(ASTM D-4157-02)

100,000 double rubs

COLOR FASTNESS TO LIGHT

50 yards

(AATCC-16A) Class 5.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc's)

conserving natural resources:

54"

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

Greenguard Gold Certified

- · Number 23850-410
- · formerly Children & Schools Gold Certified
- meets Calif 1350 High Performance Schools