# colour & design ©

# Woodlands Edge™                                       Type II

**Physical Properties:**

| Total Weight | U.S. Units | Metric Units |
|---|---|---|
| | 20 oz./LY | 619 G/PLM |
| | 13.3 oz./SQ | 451 G/PSM |
| Fabric Type | Osnaburg | |
| Material Width | 52/54" | 132/137 cm |
| Repeat | Horizontal 26" x Vertical 18" | |

---

**Federal Specifications:**

Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

---

**Fire Hazard Classification Results:**

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 10
Passes NFPA 286 Corner Burn Test

---

**Performance Features:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

---

**Environmental Attributes:**

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

---

**Permeability, Moisture and Mold:**

Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.
Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

---

**INSTALLATION NOTE**
**Woodlands Edge™** is a random match / non reversible pattern
For specifications and hanging instructions go to: www.colouranddesign.com

# colour & design ©

MADE IN USA

**W/A SUSTAINABILITY STANDARD NSF/ANSI 342**

**NSF Qualified Distributor**