

| Physical Properties: | Total Weight   | U.S. Units                    | Metric Units |
|----------------------|----------------|-------------------------------|--------------|
|                      |                | 20 oz./LY                     | 619 G/PLM    |
|                      |                | 13.3 oz./SQ                   | 451 G/PSM    |
|                      | Fabric Type    | Osnaburg                      |              |
|                      | Material Width | 52/54"                        | 132/137 cm   |
|                      | Repeat         | Horizontal 54" x Vertical 24" |              |

**Federal Specifications:** Colour&Design Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

#### Fire Hazard Classification

**Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 5; Smoke Developed: 30  
Passes NFPA 286 Corner Burn Test

#### Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

#### Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350

#### Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.  
Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

#### INSTALLATION NOTE

**YURII™** is a 53" Reversible Loose Horizontal Match  
For specifications and hanging instructions go to: [www.colouranddesign.com](http://www.colouranddesign.com)