



Physical Properties

Content: 20 oz. Type II Mylar wallcovering (Textured Emboss)
Thickness: .027"
Width: 52 - 54"
Length: 30 yards per roll
Backing: Non-woven on Mylar

Performance

Fire Rating: Class A ASTM E84
Flame Spread: Class A Index 10
Smoke Developed: 5
Meets or exceeds all requirements of Federal Specification
CCC-W-408 A/B/C/D
Tensile Strength: 50 x 55
Tear Strength: 25 x 25
Color fastness to light: 200 hours / BS782 (UK) PASS
Cold crack at 20F: Satisfactory
Surface Resistance: PASS
Abrasion Resistance: PASS
Dimensional Stability: PASS
Chemical Resistance: PASS

Cleaning: Soft rag with water or gentle detergent. Do not scrub or use abrasives.

NOTE* The assigned numerical reading & other tests referenced here are not intended to reflect hazards presented by this or any other material under actual fire conditions. Consult an architect or fire safety engineer for information on applicable building codes & reduction of fire hazards, including the use of sprinklers.

Sustainability

Printed with UV-curable inks that produce high image quality, improve productivity = time & cost savings. UV-curable printing may reduce the environmental impact of printing relative to solvent-based printing.

Manufactured in the USA

luxesurfaces

© 2020 Luxe Surfaces
All Rights Reserved